

Teknikum LKA™ Thermoplastic



APPLICATIONS

Designed for transporting different kind of chemicals. Suitable especially for food industry and hospital use.

The hose meets the FDA food contact requirements.

Material is thermoplastic, which withstands multiple heating and cooling cycles.

ADVANTAGES

- Suitable for food contact
- Safe and durable hose
- Thermoplastic properties

COMPLIANCY / STANDARD

The hose is compliant with food contact material regulations:

- FDA regulation: No. 21 CFR 177.2600.

TECHNICAL PROPERTIES

Previous versions

LKA (same reference and structure)

Structure

- Tube:
 - red
 - non-reinforced
 - TPE 732
 - hardness 55 ShA

Temperature range

-40°C...+120°C

MANUFACTURER

Teknikum Oy (Business ID FI07645274),
Nokiankatu 1, 38210, Sastamala, Finland

More information

sales@teknikum.com

www.teknikum.com

© All rights reserved by Teknikum Group
2020



ORDER REFERENCE

Product code	Ø i.d. mm	Ø o.d. mm	Weight kg/m	Length m
Delivery (thinner hose wall)				
LKA02504	2,5	4	0,01	100
LKA0305	3	5	0,01	100
LKA0407	4	7	0,03	100
LKA0508	5	8	0,03	100
LKA0609	6	9	0,04	100
LKA0710	7	10	0,04	100
LKA0812	8	12	0,06	50
LKA0913	9	13	0,07	50
LKA1014	10	14	0,08	50
LKA1116	11	16	0,11	50
LKA1217	12	17	0,11	50
LKA1318	13	18	0,12	50
LKA1520	15	20	0,14	50
LKA1823	18	23	0,16	50
Suction (with thicker hose wall)				
LKA10310	3	10	0,07	100
LKA10515	5	15	0,16	25
LKA10820	8	20	0,26	25

Other dimensions available on request.

REFERENCE IMAGE

