

SUPERVRAC



BULK MATERIALS HANDLING

Bulk tank truck discharge



APPLICATIONS

Pneumatic transport of bulk abrasive products.
Discharge from road and rail tankers and delivery to storage bins (cement, sand, limestone, coal, etc.).

ADVANTAGES

- Light weight, flexible hose that coils flat.
- Excellent resistance to abrasion.
- Static conductive tube.


COMPLEMENTARY INFORMATION

Can be used in ATEX zones.

TECHNICAL DESCRIPTION

Inner tube	wear resistant NR, black, smooth.
Reinforcement	synthetic textile
Cover	weather resistant NR, black, fabric impression.
Temperature range	-30°C => +90°C
Electrical Properties	conductive tube and cover, $R < 10^6 \Omega/m$.





ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
75.0	88.5	7	21	1.83	20	0060675
75.0	88.5	7	21	1.83	40	0060674
75.0	93.0	7	21	2.75	20	0060189
75.0	93.0	7	21	2.75	40	0060193
89.0	101.5	7	21	2.07	20	0060682
89.0	101.5	7	21	2.07	40	0060683
100.0	112.0	7	21	2.40	20	0129701
100.0	112.0	7	21	2.40	40	0129702
100.0	118.0	7	21	3.58	20	0060194
100.0	118.0	7	21	3.58	40	0060195
110.0	123.0	7	21	2.71	20	0060684
110.0	123.0	7	21	2.71	40	5006696
127.0	144.0	7	21	4.20	20	0060685
127.0	144.0	7	21	4.20	40	0060686
152.0	169.0	7	21	5.00	20	0060689
152.0	169.0	7	21	5.00	40	0060690

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

