


DF600/800 Eco SL

Our workaholics: robust and high-performance

CasaFan 
SafeLine

COMMERCIAL USE

Certified
in accordance with
Machinery Directive
2006/42/EC, part 1
for commercial use.



IP54

dust protected
splash proof



Accessory for wall
mounting **WHDF #**
96080 order separately


DF600 Eco SL IP54 #306090

DF800 Eco SL IP54 #308095

Housing, fan blade, matt black

- High-performance drum fans.
- Ideal for use in production, warehouse and shipping.
- 3 speeds by the encapsulated pressure switch. 2-pole ON/OFF switch.
- Vertical tilt adjustable in the range of 360°.
- Aluminium fan blade has been optimised from a technical airflow perspective.
- Protective grille, housing, frame and fan blade painted black.
- Stable, anti-tip tubular steel stand with rubber wheels and feet.
- Practical handle on the housing and cable winder on the reverse of the protective grille.
- Protection rating – IP54 dust- and splashproof, insulation class I.
- Optional 5 speed transformer ETWZ 1,0 #891020.
- 2.5 m rubber sheathed cable H07RN-F G 3 1.0 mm² for high mechanical loads with IP54 Schuko plug.

Product	Code No.	Housing/grille	Blade
DF800 Eco SL IP54	308095	Matt black paint	Black paint
DF600 Eco SL IP54	306090	Matt black paint	Black paint

Technical details		Dimensions (mm)	DF800	DF600	
Model	DF800	DF600	Dim. A/B	880/830	750/680
Power motor (W)	123		Dim. C/D	260/920	270/770
Voltage (V/Hz)	220–240/~50		Fan blade Ø	750	600
Number of speeds	3		Fan grille Ø	830	680
Rpm min. -1	870 max.				
Sound pressure (Lp-3 m) dB(A)	56.8	53.9			
Sound power (Lw) dB(A)	78.9	76.1			
Airflow max. (m³/h)*	15,650	13,000			
Service value (m³/min/W)	2,11	1,75			
Weight (kg)	19.3	16.3			

Ambient temperature - 10° to +42 °C. * measured in accordance with IEC 60879