

SAFETY DATA SHEET

Etra Contact Adhesive

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Etra Contact Adhesive

Product no.

10580

Unique formula identifier (UFI)

0CW0-G08S-900W-4VUH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Contact gluing

Use descriptors (UK REACH)

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Product category	Description
PC 1	Adhesives, Sealants
Process category	Description
PROC 10	Roller application or brushing
Environmental release category	Description
ERC 8a	Wide dispersive indoor use of processing aids in open systems
ERC 8d	Wide dispersive outdoor use of processing aids in open systems
ERC 8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
ERC 8f	Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

▼ **Company and address**

Etra Oy

Lampputie 2
00740 Helsinki
Finland
Tel.: +358 20 765 45
<https://www.etra.fi/en>

▼ **Contact person**

-

▼ **E-mail**

kemikaalit@etra.fi

Revision

17/10/2025

SDS Version

1.0

Date of previous version

17/10/2025 (1.0)

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 111 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

Skin Irrit. 2; H315, Causes skin irritation.

Eye Irrit. 2; H319, Causes serious eye irritation.

STOT SE 3; H335, May cause respiratory irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Highly flammable liquid and vapour. (H225)

Causes skin irritation. (H315)

Causes serious eye irritation. (H319)

May cause respiratory irritation. (H335)

May cause drowsiness or dizziness. (H336)

May cause damage to organs through prolonged or repeated exposure. (H373)

Toxic to aquatic life with long lasting effects. (H411)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Use only outdoors or in a well-ventilated area. (P271)

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing. (P305+P351+P338)

Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

Disposal

Not applicable.

Hazardous substances

reaction mass of ethylbenzene and xylene

ethyl acetate

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic

Additional labelling

EUH208, Contains Colophony. May produce an allergic reaction.

UFI: 0CW0-G08S-900W-4VUH

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
reaction mass of ethylbenzene and xylene	CAS No.: EC No.: 905-588-0 UK-REACH: Index No.:	25-40%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373	[1]
ethyl acetate	CAS No.: 141-78-6 EC No.: 205-500-4 UK-REACH: Index No.: 607-022-00-5	25-40%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic	CAS No.: 64742-49-0 EC No.: 927-510-4 UK-REACH: Index No.:	15-25%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	[15]
zinc oxide	CAS No.: 1314-13-2 EC No.: 215-222-5 UK-REACH: Index No.: 030-013-00-7	<1%	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
Colophony	CAS No.: 8050-09-7 EC No.: 232-475-7 UK-REACH: Index No.: 650-015-00-7	<1%	Skin Sens. 1, H317	[19]
cyclohexane	CAS No.: 110-82-7 EC No.: 203-806-2 UK-REACH: Index No.: 601-017-00-1	<1%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1], [3]
2,6-di-tert-butyl-p-cresol	CAS No.: 128-37-0 EC No.: 204-881-4 UK-REACH: Index No.:	<1%	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

[15] The classification as a carcinogen / mutagen will not be taken into account as the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7) (CLP, Annex VI, note P).

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Call a POISON CENTER/doctor if you feel unwell.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: ●3YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

Dry, cool and well ventilated

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

reaction mass of ethylbenzene and xylene
 Long term exposure limit (8 hours) (ppm): 50
 Long term exposure limit (8 hours) (mg/m³): 220
 Short term exposure limit (15 minutes) (ppm): 100
 Short term exposure limit (15 minutes) (mg/m³): 441
 Annotations:
 BMVG = Biological Monitoring Guidance Value exists
 Sk = Can be absorbed through the skin and lead to systemic toxicity.

ethyl acetate
 Long term exposure limit (8 hours) (ppm): 200
 Short term exposure limit (15 minutes) (ppm): 400

Colophony
 Long term exposure limit (8 hours) (mg/m³): 0,05
 Short term exposure limit (15 minutes) (mg/m³): 0,15
 Annotations:
 Sen = Capable of causing occupational asthma.

cyclohexane
 Long term exposure limit (8 hours) (ppm): 100
 Long term exposure limit (8 hours) (mg/m³): 350
 Short term exposure limit (15 minutes) (ppm): 300
 Short term exposure limit (15 minutes) (mg/m³): 1050

2,6-di-tert-butyl-p-cresol
 Long term exposure limit (8 hours) (mg/m³): 10

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
 EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

2,6-di-tert-butyl-p-cresol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	5 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	8,3 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	1,74 mg/m ³
Long term – Systemic effects - Workers	Inhalation	5,8 mg/m ³

ethyl acetate

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	63 mg/kg bw/day

PNEC

2,6-di-tert-butyl-p-cresol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0,004 mg/L
Intermittent release		0,004 mg/L

Marine water	0,0004 mg/L
Sewage treatment plant	100 mg/L
Soil	1,04 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure


Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment


Generally

Use only UKCA marked protective equipment.


Respiratory Equipment

Work situation	Type	Class	Colour	Standards	
In case of insufficient ventilation	A	Class 2 (medium capacity)	Brown	EN14387	


Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.5	> 30	EN374-2, EN374-3, EN388	

Eye protection

Work situation	Type	Standards	
When there is a risk of getting product in eyes	Wear safety glasses with side shields.	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Yellow

Odour / Odour threshold

No data available.

pH

No data available.

Density (g/cm³)

0.87

Kinematic viscosity

No data available.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

No data available.

Softening point/range (°C)

Does not apply to liquids.

Boiling point (°C)

104

Vapour pressure

No data available.

Relative vapour density

No data available.

Decomposition temperature (°C)

No data available.

Data on fire and explosion hazards

Flash point (°C)

7

Flammability (°C)

The material is ignitable.

Auto-ignition temperature (°C)

No data available.

Lower and upper explosion limit (% v/v)

No data available.

Solubility

Solubility in water

Insoluble

n-octanol/water coefficient (LogKow)

No data available.

Solubility in fat (g/L)

No data available.

9.2. Other information

Oxidizing properties

No data available.

Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

Acute toxicity

Product/substance	ethyl acetate
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	5600 mg/kg ·

Product/substance	ethyl acetate
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	56000 mg/l/4h ·

Product/substance	zinc oxide
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	2500 mg/min ·

Product/substance	zinc oxide
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	7950 mg/kg ·

Product/substance	cyclohexane
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	5000 mg/kg ·

Based on available data for the mixture, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data for the mixture, the classification criteria are not met.

Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

Germ cell mutagenicity

Based on available data for the mixture, the classification criteria are not met.

Carcinogenicity

Based on available data for the mixture, the classification criteria are not met.

Reproductive toxicity

Based on available data for the mixture, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data for the mixture, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.
Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

reaction mass of ethylbenzene and xylene has been classified by IARC as a group 3 carcinogen.
2,6-di-tert-butyl-p-cresol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance ethyl acetate
Species: Fish
Duration: 96 hours
Test: LC50
Result: >200 mg/l ·

Product/substance ethyl acetate
Species: Daphnia
Duration: 48 hours
Test: EC50
Result: >700 mg/l ·

Product/substance ethyl acetate
Species: Algae
Duration: 72 hours
Test: IC50
Result: >100 mg/l ·

Product/substance ethyl acetate
Species: Daphnia, Daphnia magna
Duration: 24 hours
Test: EC50
Result: 2500-3090 mg/L

Product/substance ethyl acetate
Species: Daphnia, Daphnia magna
Duration: 21 days
Test: NOEC
Result: 2,4 mg/L

Product/substance zinc oxide
 Species: Daphnia
 Duration: 48 hours
 Test: EC50
 Result: >1000 mg/l ·

Product/substance zinc oxide
 Species: Fish
 Duration: 96 hours
 Test: LC50
 Result: 1,1 mg/l ·

Product/substance zinc oxide
 Species: Algae
 Duration: 72 hours
 Test: EC50
 Result: 0,17 mg/l ·

Product/substance cyclohexane
 Species: Daphnia
 Duration: 48 hours
 Test: EC50
 Result: 0,9 mg/l ·

Product/substance 2,6-di-tert-butyl-p-cresol
 Species: Fish, Danio rerio
 Duration: 96 hours
 Test: LCLo
 Result: > 0,57 mg/L

Product/substance 2,6-di-tert-butyl-p-cresol
 Species: Daphnia, Daphnia magna
 Duration: 48 hours
 Test: LC50
 Result: 0,61 mg/L

Product/substance 2,6-di-tert-butyl-p-cresol
 Species: Algae, Desmodesmus subspicatus
 Duration: 72 hours
 Test: IC50
 Result: > 0,4 mg/L

Product/substance 2,6-di-tert-butyl-p-cresol
 Species: Bacteria
 Duration: 3 hours
 Test: EC50
 Result: > 10000 mg/L

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Product/substance ethyl acetate
 Conclusion: Readily biodegradable

Product/substance 2,6-di-tert-butyl-p-cresol
 Duration: 28 days
 Result: 4,5 %
 Conclusion: Not biodegradable
 Test: OECD 301 C

12.3. Bioaccumulative potential

Based on available data for the mixture, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 6 - Acute toxicity

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code





08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informatio n:
ADR	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1  	II	Yes	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1  	II	Yes	Limited quantities: 5 L EmS: F-E S-D See below for additional information.

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
IATA	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1  	II	Yes	See below for additional information.

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

Hazchem Code: ●3YE

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

Control of Major Accident Hazards (COMAH) - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

E2 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 200 tonnes / (upper-tier): 500 tonnes

UK-REACH, Annex XVII

cyclohexane is subject to restrictions, UK-REACH annex XVII (entry 57).

reaction mass of ethylbenzene and xylene is subject to UK-REACH restrictions (entry 40).

ethyl acetate is subject to UK-REACH restrictions (entry 40).

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic is subject to UK-REACH restrictions (entry 40).

cyclohexane is subject to UK-REACH restrictions (entry 40).

Additional information

Tactile warning.

Sources

The Management of Health and Safety at Work Regulations 1999.

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.
H225, Highly flammable liquid and vapour.
H226, Flammable liquid and vapour.
H304, May be fatal if swallowed and enters airways.
H312, Harmful in contact with skin.
H315, Causes skin irritation.
H317, May cause an allergic skin reaction.
H319, Causes serious eye irritation.
H332, Harmful if inhaled.
H335, May cause respiratory irritation.
H336, May cause drowsiness or dizziness.
H373, May cause damage to organs through prolonged or repeated exposure.
H400, Very toxic to aquatic life.
H410, Very toxic to aquatic life with long lasting effects.
H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)
LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
PROC 10 = Roller application or brushing
PC 1 = Adhesives, Sealants
ERC 8a = Wide dispersive indoor use of processing aids in open systems
ERC 8d = Wide dispersive outdoor use of processing aids in open systems
ERC 8c = Wide dispersive indoor use resulting in inclusion into or onto a matrix
ERC 8f = Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
CAS = Chemical Abstracts Service
CE = Conformité Européenne (European conformity)
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CSA = Chemical Safety Assessment
CSR = Chemical Safety Report
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EINECS = European Inventory of Existing Commercial chemical Substances
ES = Exposure Scenario
EUH statement = CLP-specific Hazard statement
EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of

1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Product Safety Department

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en