

Product information

MOVING YOUR WORLD



RENOLIT CG 92

Grease / Chassis grease

Description

RENOLIT CG 92 is a high-quality calcium thickened grease with good water resistance. It is intended for heavily loaded plain and roller bearings. The product is suitable for lubrication within both industrial and demanded automotive applications.

Application

RENOLIT CG 92 is recommended for the lubrication of chassis, construction, agricultural and forestry machines, water pumps and similar. The product is also recommended in industrial and marine applications where a mechanical stable and water-resistant grease with corrosion protection properties is required. The product can be used especially in applications exposed to demanding conditions with frequent washing over with water. RENOLIT CG 92 provides extended lubrication intervals due to optimised properties and performance. The product is recommended within the temperature range -30°C to +120°C, max +130°C. Suitable for up to 2/3 of the speed range according to the main SKF catalogue.

Advantages / Benefits

- RENOLIT CG 92 contains additives that protect against wear, oxidation and corrosion.
- The product has a high load-carrying capacity, is mechanically stable, gives excellent corrosion protection and very good water resistance.
- RENOLIT CG 92 can withstand high loads for an extended period.
- RENOLIT CG 92 offers very good adhesion.
- The product is a very good alternative in applications exposed to demanding weather conditions.
- RENOLIT CG 92 is easily pumped in most modern central lubrication systems, despite its relatively high base oil viscosity. At low temperatures is RENOLIT CG 90 recommended.

Classification

ISO 12924: L-XC(F)CIB2
DIN 51502: KP2K-30

2024-03

Product information

MOVING YOUR WORLD



Handling and storage

Avoid skin contact. In the event of contact with skin, wash with soap and water. Dispose of used grease at a recycling station or equivalent. Safety data sheets are available on www.fuchs.com/se or supplied on request.

Typical data

Characteristics	Method	Value
NLGI grade	ASTM D 217	2
4-ball, WL	DIN 51350:4	3200 N
Base oil viscosity at 100°C	ASTM D 7152	95 mm ² /s
Base oil viscosity at 40 °C	ASTM D 7152	1350 mm ² /s
Penetration, worked 60 strokes	ISO 2137	265 -295 mm/10
Water resistance at 90°C	DIN 51807:1	0
Thickener	-	Calcium soap

The information contained in this product information is based on the experience and know-how of FUCHS in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend that you consult a FUCHS LUBRICANTS SWEDEN AB application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS SWEDEN AB
© FUCHS LUBRICANTS SWEDEN AB. All rights reserved.

2024-03