

WHE00104

EN



TECHNICAL DETAILS



STANDARD

EN 397 | -30°C / LD / MM



EN 12492

for the following clauses only:

Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact,
4.2.1.4 rear impact
4.2.2 | Penetration



TEMPERATURE OF USE

-30°C / +50°C



WEIGHT

390 g



SIZE

Universal-adjustable from 51 to 63 cm



MATERIAL

EXTERNAL SHELL:
HD Polypropylene



INTERNAL SHELL:

Neopor® Cycled® by BASF | EPS obtained from chemical recycling of plastic waste.

WHE00104-201 WHITE	WHE00104-206 BRITISH GREEN
WHE00104-202 YELLOW	WHE00104-207 ROYAL
WHE00104-203 ORANGE	WHE00104-208 BLUE
WHE00104-204 RED	WHE00104-210 BLACK
WHE00104-205 GREEN	WHE00104-214 PINK



CATEGORY

II

HEADBAND:

Soft PA Nylon

TECHNOLOGIES



HD EPS INTERNAL SHELL

Inner shell composed of high-density Neopor® Cycled® foam for all-around impact energy absorption and improved comfort.



RING TO HOOK

Chinstrap loop that enables the wearer to securely attach the helmet to a harness or other items.



2DRY LINER

A quick-drying fabric with moisture-wicking technology that accelerates the dispersion of sweat to the surface of the helmet padding for a drier, more comfortable wear.



EARMUFF ADAPTER ATTACHMENT POINTS

Helmet designed with attachment points for earmuff adapters. It allows KASK earmuffs to be integrated with helmet.



QUICK FIT SYSTEM

Size adjustment system for maximum stability, easy to use thanks to a large diameter wheel.



VISOR ATTACHMENT POINTS

Helmet designed with attachment points for securing KASK eye protection accessories.



VENTILATION CHANNELS

Helmet designed with 10 air intakes that maximize internal airflow through outflow channels providing exceptional helmet breathability.



INTEGRATED LAMP CLIPS

Designed with 4 built-in, nylon lamp attachment points. Compatible with KASK headlamps and other headlamps with elastic bands.



ANTI-INTRUSION MESH

Metal mesh vent covers that prevent debris from entering the ventilation channels while maintaining breathability.

PERFORMANCES

Protection against top impacts	K	5 kg from 1 m 50 J
Protection against front, lateral and rear impacts	K	5 kg from 0,5 m 25 J
Protection against penetration of objects	K	3 kg from 1 m 30 J
Chinstrap release	K	>15 kg <25 kg

Lower temperature resistance test	K	T= -30°C
Protection against side deformation	K	LD
Protection against molten metal splashes	K	MM

K EN 397 standard requirements

K Additional tests in conformity with EN 12492 requirements

K EN 397 optional requirements



Since 2019, every KASK helmet made has been tested with the KASK Rotational Impact WG11 Test. All KASK helmets have BrIC values <0.39.

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

LIFE SPAN

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage.

CLEANING

Clean the helmet with the KASK Helmet cleaner or with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

STORAGE

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of the KASK drawstring helmet bag to protect the helmet when not in use.

ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.

3
YEARS
GUARANTEE

10
YEARS
LIFE SPAN



SCAN FOR
COMPLETE
COLLECTION