



# DuPont™ Tychem® 6000 Tape

The Next-Level Chemical  
Barrier Connection

## SUPERIOR CHEMICAL BARRIER

- Provides a permeation barrier of at least 30 minutes against hazards, including toxic industrial chemicals and highly concentrated organic solvents.\*.
- Provides seamless protection—no weak links between tape and suit, helping maintain the garment's intended chemical barrier performance at every junction.



\*Please check DuPont™ SafeSPEC™ for permeation data.



## HAND-TEARABLE; LOW ELONGATION; NO CURLING

- Fast, easy application with a secure fit.
- Lightweight for ease of use

## SUITABLE FOR USE WITH CATEGORY III CHEMICAL PROTECTIVE GARMENTS, INCLUDING TYCHEM®, TYVEK®, AND PROSHIELD®

- Reliable adhesion in challenging environments—tape stays in place, even on dusty surfaces, so your PPE remains uncompromised.
- Typically functions as a connection between gloves and Category III Tychem®, Tyvek® or ProShield® chemical protective garments. It can further be used to tape the hood to the mask, the ankles to the boots and the zipper flap.

NOTES: • This tape does not protect against ionizing radiation.  
• This tape is not flame resistant and should not be used in areas with heat, open flame, sparks or in potentially flammable environments.



Category I

<b>Reference:</b>	TF00990YL00
<b>Colour:</b>	Yellow
<b>Dimensions:</b>	Width 50 mm x Length 50 m per roll
<b>Packaging:</b>	12 rolls per box



chemical spill clean-up,  
petrochemical industry tasks



emergency  
response



maintenance  
operations



laboratories



### Want to Explore More?

Visit the DuPont™ SafeSPEC™ page to review technical data or request a sample.

[safespec.dupont.co.uk](https://safespec.dupont.co.uk)



[tyvek.com/ppe](https://tyvek.com/ppe)

### Connect with us:

This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience become available. It is the user's responsibility to determine the level of toxicity and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. This information is intended for use by persons having the technical expertise to undertake evaluation under their own specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first check that the garment selected is suitable for the intended use. The end-user should discontinue use of garment if fabric becomes torn, worn or punctured, to avoid potential chemical exposure. Since conditions of use are beyond our control, DUPONT DE NEMOURS, INC. AND ITS AFFILIATES MAKE NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THESE PRODUCTS AND INFORMATION. This information is not intended as a license to operate under or a recommendation to infringe any trademark, patent or technical information of DuPont or other persons covering any material or its use.

© 2026 DuPont. All rights reserved. DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.