



EAN:	4013288158352	Size:	100x60x10 mm
Part number:	05073906001	Weight:	10 g
Article number:	840/1 IMP DC SB Impaktor Bits SiS	Country of origin:	CZ
		Customs tariff number:	82079030

- For hexagonal socket head screws
- Impaktor technology for an above-average service life even under extreme demands
- Particularly suitable for use with customary impact drivers
- Diamond coating for a secure fit in the screw, literally bites into the screwhead to prevent cam-out
- 1/4" hexagon drive (Wera connecting series 1)
- Take it easy tool finder: colour coding according to profile and size

High quality Impaktor bits for hexagon socket screws. The Impaktor technology offers an above-average service life even under extreme circumstances. Enhanced friction resistance, thanks to the rough diamond-particle coating on the bit tip, prevents any slipping out of the screw head. Hex-Plus ensures a greater contact surface in the head of the screw. The notching effect is therefore reduced to a minimum and damage to the screw head more or less eliminated. 1/4" hexagon, suitable for holders as per DIN ISO 1173-D 6.3.

Web link
<https://www.wera.de/en/05073906001>

Wera - 840/1 IMP DC SB Impaktor Bits SiS
 05073906001 - 4013288158352

Wera Werkzeuge GmbH
 Korzter Straße 21-25
 D-42349 Wuppertal
 Tel: +49 (0)2 02 / 40 45-0
 E-Mail: info@wera.de

Impaktor-Bits



Impaktor technology for an above-average service life even under extreme demands



For an above-average service life. Maximum utilisation of the material properties, a very special geometry - designed particularly to meet the extreme demands - as well as a specific manufacturing process mean that Wera Impaktor tools have an above-average service life. Another product advantage is the coating of the Impaktor bits with minute diamond particles. These diamond particles reduce the cam-out effects - particularly high in power tool applications - which can lead to a slipping out of the screw head. The diamond particles literally bite themselves into the screw recess. This means that less contact pressure is required, something that greatly delays fatigue setting-in in power tool screwdriving jobs.

Improved productivity



For use with impact screwdrivers. Improve productivity when screwdriving with power tools.

Above-average service life



Maximum utilisation of the material properties, a very special geometry - designed particularly to meet the extreme demands - as well as a specific manufacturing process mean that Wera Impaktor tools have an above-average service life.

Web link

<https://www.wera.de/en/05073906001>

Wera - 840/1 IMP DC SB Impaktor Bits SiS
05073906001 - 4013288158352

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

Reduced danger of bit breakage.



Particularly high strength. Reduce the danger of premature bit breakage.

Torsion zone



Torsion zone specially designed to absorb such forces and thereby protect the bit tip.

Hex-Plus



Hexagon socket screws are a problem, because the contact surfaces that transfer the force of the tool to the screw are very narrow. The consequence: the head of the screw can be damaged, usually rounding out the recess. Hex-Plus tools have larger contact surfaces to prevent this, driving from the flats of the recess, rather than the corners. Good to know: Hex-Plus tools fit into every standard hexagon socket screw!

Bits with Take it easy tool finder



Take it easy tool finder with colour coding according to profiles and size stamp - for simple and rapid accessing of the required tool.

Web link

<https://www.wera.de/en/05073906001>

Wera - 840/1 IMP DC SB Impaktor Bits SiS
05073906001 - 4013288158352

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de

840/1 IMP DC SB Impaktor bits, 6 x 25 mm

Set contents:

840/1 IMP DC Impaktor bits, 6 x 25 mm



1x 6 x 25 mm



Web link

<https://www.wera.de/en/05073906001>

Wera - 840/1 IMP DC SB Impaktor Bits SiS
05073906001 - 4013288158352

Wera Werkzeuge GmbH
Korzter Straße 21-25
D-42349 Wuppertal
Tel: +49 (0)2 02 / 40 45-0
E-Mail: info@wera.de