



<b>EAN:</b>	4013288158413	<b>Size:</b>	100x60x10 mm
<b>Part number:</b>	05073926001	<b>Weight:</b>	9 g
<b>Article number:</b>	867/1 IMP DC SB SiS	<b>Country of origin:</b>	CZ
		<b>Customs tariff number:</b>	82079030

- For recessed TORX® screws
- Impaktor technology for above-average service life
- Particularly suitable for use with customary impact drivers
- Diamond coating for a secure fit in the screw, literally bites into the screwhead to prevent cam-out
- 1/4" hexagon drive (Wera connecting series 1)
- Take it easy tool finder: colour coding according to profile and size

High quality bits for recessed TORX® screws. The Impaktor technology offers an above-average service life even under extreme circumstances. Enhanced friction resistance, thanks to the rough diamond-particle coating on the bit tip, prevents any slipping out of the screw head. Particularly suitable for use with customary impact drivers. 1/4" hexagon, suitable for holders as per DIN ISO 1173-D 6.3.

#### Web link

<https://www.wera.de/en/05073926001>

Wera - 867/1 IMP DC SB SiS  
05073926001 - 4013288158413

Wera Werkzeuge GmbH  
Korzerter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

### Impaktor-Bits



Impaktor technology for an above-average service life even under extreme demands



For an above-average service life. Maximum utilisation of the material properties, a very special geometry - designed particularly to meet the extreme demands - as well as a specific manufacturing process mean that Wera Impaktor tools have an above-average service life. Another product advantage is the coating of the Impaktor bits with minute diamond particles. These diamond particles reduce the cam-out effects - particularly high in power tool applications - which can lead to a slipping out of the screw head. The diamond particles literally bite themselves into the screw recess. This means that less contact pressure is required, something that greatly delays fatigue setting-in in power tool screwdriving jobs.

### Improved productivity



For use with impact screwdrivers. Improve productivity when screwdriving with power tools.

### Above-average service life



Maximum utilisation of the material properties, a very special geometry - designed particularly to meet the extreme demands - as well as a specific manufacturing process mean that Wera Impaktor tools have an above-average service life.


#### Web link

<https://www.wera.de/en/05073926001>

Wera - 867/1 IMP DC SB SiS  
05073926001 - 4013288158413

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)

**Reduced danger of bit breakage.**




Particularly high strength. Reduce the danger of premature bit breakage.

**Torsion zone**



Torsion zone specially designed to absorb such forces and thereby protect the bit tip.

**Reduced contact pressure**



These diamond particles reduce the cam-out effects - particularly high in power tool applications - which can lead to a slipping out of the screw head. The diamond particles literally bite themselves into the screw recess. This means that less contact pressure is required, something that greatly delays fatigue setting-in in power tool screwdriving jobs.

**Bits with Take it easy tool finder**



Take it easy tool finder with colour coding according to profiles and size stamp - for simple and rapid accessing of the required tool.

**Web link**  
<https://www.wera.de/en/05073926001>

Wera - 867/1 IMP DC SB SiS  
 05073926001 - 4013288158413

Wera Werkzeuge GmbH  
 Korzter Straße 21-25  
 D-42349 Wuppertal  
 Tel: +49 (0)2 02 / 40 45-0  
 E-Mail: info@wera.de

Set contents:

867/1 IMP DC Impaktor TORX® bits, TX 30 x 25 mm



1x TX 30 x 25 mm



Web link

<https://www.wera.de/en/05073926001>

Wera - 867/1 IMP DC SB SiS  
05073926001 - 4013288158413

Wera Werkzeuge GmbH  
Korzter Straße 21-25  
D-42349 Wuppertal  
Tel: +49 (0)2 02 / 40 45-0  
E-Mail: [info@wera.de](mailto:info@wera.de)